

428 McCormick Street
San Leandro, CA 94577
510-567-8503
510-567-8506 [fax]
www.inexinnovation.com

Dealer and Distributor
Please Contact:
510-326-2985
jimmyko@inexinnovation.com



PRE-A200

General Specifications

Parameter	Specification
Frequency Response	4 Hz to 30 MHz
Maximum Output	2.5 volts unbalanced 5.0 volts balanced
Sensitivity	Unbalanced Line Level Inputs 2.5 volts Balanced Inputs 5.0 volts
XLR Connector Pin-out (Balanced I/O)	pin 1 ground, pin 2 positive, pin 3 negative
Audio Signal I/O	2 pairs of RCA inputs 2 pairs of RCA outputs 2 pairs of balanced female XLR inputs 1 pair of balanced male XLR outputs
Line Power	100 - 240 VAC
Remote Control Battery	Two AAA
Dimensions L x W x H	16.5 x 14 x 4.5 inches 420 x 360 x 110 mm
Weight	16 pounds / 7.3 kg

Order Information

Part Number	Description
PRE-A200	Photon PreAmp

The information set forth in this document reflects our best knowledge at the time of issue. The document is subject to changes pursuant to new developments and findings, and a similar reservation applies to the properties of the products described. We undertake no liability for results obtained by usage of our products and information.